MEDICAL IMAGING
CSO Customer Support Operations

Fieldservice Bulletin

Order-No.: DD+DIS205.99E

1 Piece QF5KT MA1

October 99

ADC System
Type 5145, 5155

Please file this document in section 13 of your technical documentation ADC Compact/Solo.

New PC-Hardware for PRID - Station

Since September 1999, a new hardware configuration for the PRID – Station is delivered.

The new configuration of the PRID - PC is as follows :

- Type : COMPAQ DESKPRO EN SFF 6450+
- Processor : PentiumIII / 450/100 MHz - 512KB L2 Cache - 256MB RAM
- HardDisk : 10GB ULTRA ATA
- CD-ROM : IDE SLIMLINE CD-ROM 24x-
- FloppyDrive : 1.4MB
- Video : Embedded ATI RAGE PRO TURBO 2X AGP GRAPHICS with 4MB SGRAM (MAX 8MB)
- Monitor : 17"
- Network : Embedded 10/100 TX INTEL WOL 24 UTP PCI NIC
- Audio : Integrated ESS 1869 FULL DUPLX 16BIT AUDIO WITH INTERN. SPKR
- Case : Number of slots: 1 PCI / 1PCI-ISA / 3BAYS
- Heat emission (Watts):
  - PC < 100 W
  - Monitor (Compaq 17" V75) * < 115 W
  - Monitor (Compaq 17" V700) ** < 130 W

  * phase-out model
  ** follow-up model to V75

printed in Germany

AGFA

- Dimensions (WxHxD / cm):
  - PC 31.8 x 9.0 x 37.1
  - Monitor (Compaq 17" V75) * 42.1 x 43.5 x 43.6
  - Monitor (Compaq 17" V700) ** 42.4 x 44.4 x 43.1

- Weight: (kg)
  - PC approx. 9.1 kg
  - Monitor (Compaq 17" V75) * 22.0 kg
  - Monitor (Compaq 17" V700) ** 18.5 kg

- Software : COMPAQ RESTORE CD + WIN/NT 4.0 + MS Service Pack 5

* phase-out model
** follow-up model to V75